



A QPE Product with Blended Gage Observations and High-Resolution WRF Ensemble Model Output: Comparison with Analyses and Verification during the HMT-ARB



Edward I. Tollerud¹, John A. McGinlev¹, Steven L. Mullen², Tomislava Vukicevic³, Huiling Yuan³, Chungu Lu⁴, and Isidora Jankov⁴

1NOAA Earth System Research Laboratory (ESRL), Global Systems Division Boulder, Colorado USA 2Department of Atmospheric Sciences, University of Arizona, Tucson, Arizona USA 3Cooperative Institute for Research in Environmental Sciences (CIRES), University of Colorado at Boulder, and Earth System Research Laboratory (ESRL), Global Systems Division, Boulder, Colorado 4Cooperative Institute for Research in the Atmosphere, Colorado State University, Fort Collins, Colorado USA, and Earth System Research Laboratory (ESRL), Global Systems Division, Boulder, Colorado USA



1. Introduction

Particularly in regions of extreme terrain, timely quantitative precipitation estimates (QPE) during heavy rainfall/snowfall events are critical but difficult to obtain given instrumentation density and quality issues. For these situations, it is possible that a blend of short-term forecasts with observations might perform better than purely observational estimates. In this paper, we describe an example of this kind of system, one which applies variationally-driven ensemble methods to blend WRF forecasts with gage measurements. We apply them to a case of very heavy precipitation in the Northern California Sierra Nevada Mountains during December and January of 2005-6.




2. Domain, Methods, Observations, and Models


- Severe Terrain and orographic precipitation dominate over American River Basin
- IOP4 (12/31/2005-01/02/2006) produced most extreme precipitation during HMT1
- Mean and Covariance computed from solution to


$$x_a = x_b + (HP_fH^T + R)^1 H^T R^{-1} (y - Hx_b)$$

$$P_a = (H^T R^{-1} H + P_e^{-1})^{-1}$$


- Background added to ensemble forecast members to ensure stability of solution
- Blended observations are HADS gage observations summed over 6h intervals
- 3-5 gage gages withheld from each ensemble member for verification purposes
- Time-lagged and multi-model (mixed microphysics) ensemble members (WRF)
- Quality of QPE depends on lag number and background ratio (alpha); (left below)
- Five runs with random withheld gages were made, giving ~183 verification pairs








ensemble mean with verify auage se



3. Results

- Stage IV analyses (panels directly above) smooth relative to ensemble mean forecast and blended product (QPE)
- QPE fields appear to retain finer model-scale terrain features, especially the east-west ridges (directly above)
- Randomized withholding of ~10% of gages has small effect on the QPE field patterns (far upper right panels)
- STMAS gage-only analyses suffer in regions of scarce or missing gage observations (Lake Tahoe; far upper right) Poor forecast timing in scenarios of general light precipitation result in spurious extreme rainfall maxima (right
- Ensemble mean forecast scatter points cluster above 1:1 line on scatter plot, indicating a tendency to over-forecast
- STMAS correlation coefficients are below those of QPE and those of ensemble mean model forecasts
- Domain-averaged rainfall greatest for ensemble mean, indicating strong over-forecast (lower left color bar plots)
- Both QPE and STMAS provide unbiased estimates as compared gage observations (lower left color bar plots)
- Mean absolute errors (MAE) for STMAS and ensemble forecasts are similar; QPE values of MAE are ~25% better
- RMSE values for QPE are superior to both those of the ensemble mean and gage-only analyses (STMAS in this case)
- Equitable threat scores (ETS) for QPE superior to STMAS gage only analysis and ensemble mean (directly below)



4. Conclusions and Further Research

- · Blended model/observation QPE fields verify favorably compared to observation-only analyses (STMAS)
- •The inclusion of short-period model fields helps to capture model physics and terrain effects
- Sensitivity studies needed to test performance in other storms and for other precipitation scenarios
- Rigorous comparison with other methods to produce QPE fields is needed
- Improvements to computational efficiency (to avoid matrix inversion) are possible
- Impact of observational error estimates and number of lagged ensemble members should be done
- Extensions to input observations could include gridded precipitation estimates from radar and satellite
- Possible applications include techniques to define 'optimum' geographical distributions of rain gages
- Plans are being developed to apply the technique to land-falling hurricanes during the HMT-SE

